

SKY15

Door- or wall-mount air conditioners

COOLING CAPACITY

1550 W




Features	UoM	SKY15BT0B	SKY15CT0B	SKY15GT0B
Cooling capacity EN14511 - A35A35	W	1550	1550	1550
Cooling capacity EN14511 - A35A50	W	1200	1200	1200
Power supply	V - Hz	230 1~ 50-60	115 1~ 50-60	400/440 2~50-60
Width	mm	400	400	400
Height	mm	950	950	950
Depth	mm	233	233	233
Max current	A	5.3	12.9	2.9
Inrush current	A	18	39	11
T Fuse	A	10	20	6
Power draw EN14511 - A35A35	W	880	900	900
Power draw EN14511 -A35A50	W	980	1000	1000
Operating cycle	-	100%	100%	100%
Electrical connection	-	4-pin plug	4-pin plug	4-pin plug
R134a Refrigerant	kg	0.44	0.44	0.44
Max refrigeration circuit pressure	bar	25	25	25
External air fan capacity	m ³ /h	1050	1050	1050
Cabinet air fan capacity	m ³ /h	570	570	570
Internal temperature range	°C	20-46	20-46	20-46
Temperature regulation	-	Electronic thermostat, factory set to 35°C		
External temperature range	°C	20-55*	20-50	20-50
EN60529 ingress protection - cabinet side	-	IP54	IP54	IP54
EN60529 ingress protection - ambient side	-	IP34	IP34	IP34
Noise level	dB (A)	65	65	65
Weight	kg	38	40	40
Colour	-	RAL 7035 embossed effect		
Conformity	-	CE	CE	CE

Accessories

Pack of 5 fabric air filters	C15000181
Pack of 1 metal air filter	C15000182
External stainless-steel framework	
Coating in non-standard colour	

* 50 °C at 60 Hz

Performance



- P = Cooling capacity (W)
- Ta = Ambient Temperature (°C)
- Ti = Internal cabinet temperature (°C)

Dimensions

