

# ACCESSORIES

## HUMIDISTAT



| Features                             | UoM | AAWHS10                                      |
|--------------------------------------|-----|--|
| Operating temperature                | °C  | 0-60   |
| Field of regulation                  | %RH | 35-95  |
| Activation differential              | %RH | 4  |
| Contact                              | -   | Change-over                                  |
| Contact capacity with resistive load | A   | 5  |
| Max voltage                          | V   | 250 AC                                       |
| Dimensions HxWxD                     | mm  | 67x50x38                                     |
| Max permissible air speed            | m/s | 15   |
| Electrical connection                | -   | 3-pole terminal board (2.5 mm <sup>2</sup> ) |
| Operating temperature limit          | °C  | 0+60   |
| IP rating EN60529                    | -   | IP20   |
| Clip installation for DIN rail       | mm  | 35   |
| Conformity                           | -   | CE   |

### Accessories

Pack of 5 x device  
installation accessories  
for cabinets

- AAWFT10

## AAWHS10

### Humidistat

Humidistat which allows the formation of condensation to be prevented, protecting the inside of the cabinet from the resulting inevitable damage. Used to control anti-condensate heaters or dehumidifiers. Features a change-over contact with high switching power.

LOAD 2 = ELECTRICAL CABINET HEATING  
LOAD 3 = DEHUMIDIFIER

